

## Flat gaskets, metric, PG, NPT, GAS

Type **SVN4**

Type SVN4 - Flat thread gasket, metric/NPT/PG/GAS



Order no.	Fits to thread metric	Inside Ø (mm)	Outside Ø (mm)	Thickness (mm)	PU (pcs)
SVN4-M12.50	M12 x 1.5	12.0	20.0	1.5	50
SVN4-M12/02.50	M12 x 1.5	12.0	23.0	1.5	50
SVN4-M16.50	M16 x 1.5	16.0	22.0	1.5	50
SVN4-M16/02.50	M16 x 1.5	16.0	25.0	1.5	50
SVN4-M20.50	M20 x 1.5	20.0	27.0	1.5	50
SVN4-M20/02.50	M20 x 1.5	20.0	33.0	1.5	50
SVN4-M25.30	M25 x 1.5	25.0	35.0	1.5	30
SVN4-M25/01.30	M25 x 1.5	25.0	31.0	1.5	30
SVN4-M25/02.30	M25 x 1.5	25.0	39.0	1.5	30
SVN4-M32.20	M32 x 1.5	32.0	43.0	1.5	20
SVN4-M32/02.20	M32 x 1.5	32.0	49.0	1.5	20
SVN4-M40.20	M40 x 1.5	40.0	55.0	1.5	20
SVN4-M40/01.20	M40 x 1.5	40.0	51.0	1.5	20
SVN4-M40/02.20	M40 x 1.5	40.0	64.0	1.5	20
SVN4-M50.10	M50 x 1.5	50.0	69.0	1.5	10
SVN4-M50/01.10	M50 x 1.5	50.0	59.0	1.5	10
SVN4-M50/02.10	M50 x 1.5	50.0	74.0	1.5	10
SVN4-M63.10	M63 x 1.5	63.0	75.0	1.5	10

Order no.	Fits to thread PG	Inside Ø (mm)	Outside Ø (mm)	Thickness (mm)	PU (pcs)
SVN4-07.50	07	12.5	16.5	1.5	50
SVN4-09.50	07	15.2	20.0	1.5	50
SVN4-11.50	11	18.6	24.0	1.5	50
SVN4-13.50	13.5	20.4	31.0	1.5	50
SVN4-16.50	16	22.5	31.0	1.5	50
SVN4-21.30	21	28.3	37.0	1.5	30
SVN4-29.30	29	37.0	48.0	1.5	20
SVN4-36.20	36	47.0	57.0	1.5	20
SVN4-42.10	42	54.0	60.0	1.5	10
SVN4-48.10	48	59.3	69.0	1.5	10

Order no.	Fits to thread NPT	Inside Ø (mm)	Outside Ø (mm)	Thickness (mm)	PU (pcs)
SVN4-N02/01.50	½"	21.6	28.0	1.5	50
SVN4-N04/01.30	¾"	27.0	36.0	1.5	30
SVN4-N06/01.20	1"	33.7	46.0	1.5	20
SVN4-N07/01.20	1¼"	42.5	55.0	1.5	20
SVN4-N08/01.10	1½"	48.6	70.0	1.5	10
SVN4-N09/01.10	2"	60.7	70.0	1.5	10

Order no.	Fits to thread GAS	Inside Ø (mm)	Outside Ø (mm)	Thickness (mm)	PU (pcs)
SVN4-G00.50	¼"	13.2	20.0	1.5	50
SVN4-G01.50	½"	16.7	22.0	1.5	50
SVN4-G02.50	¾"	21.0	28.0	1.5	50
SVN4-G04.30	¾"	26.5	34.0	1.5	30
SVN4-G06.20	1"	33.3	42.0	1.5	20
SVN4-G07.20	1¼"	41.9	53.0	1.5	10
SVN4-G08.10	1½"	47.8	62.0	1.5	20
SVN4-G09.10	2"	59.6	69.0	1.5	10

For sealing of polyamide or metal threads of PMA fittings. For ingress protection at the thread up to IP68

For solid sealing of uneven rough contact areas around the thread hole or when no constructive measures for O-Rings are provided

NBR reinforced with aramide fibres (asbestos-free). Temperature range: -50°C to +200°C, short-term to +350°C

Note: Depending on flange sizes flat thread gaskets can have different widths. Please indicate fitting for which gasket is needed for replacement orders