



blueglobe – Plastic

Polyamide, colours: grey (RAL 7035), black (RAL 9011)

Metric connection thread according to EN 60423

Without connection thread sealing ring

Type of protection IP 68 up to 15 bar, IP 69, Type 4X

Strain relief up to class B, EN 62444



[Request sample](#)

Material gland body	Version/colour	Material sealing insert	Colour	Temperature range (min./max.)
PA 6.6	Black	TPE	Blue	-20 °C / +120 °C

Art. No.	Amount		Connection thread/length		Sealing range	Sealing range without inlet	Sealing range with inlet	Mounting height	Spanner width		Conformity
			A	D mm							
bg 212PAn	1		M12x1.5	8.0	7.5 – 2.0	7.5 – 5.0	5.0 – 2.0	23.0	17x19.5	50	RoHS CE
bg 216PAn	1		M16x1.5	9.0	11.0 – 4.0	11.0 – 7.0	7.0 – 4.0	27.0	20x22.8	50	RoHS CE
bg 220PAn	1		M20x1.5	9.0	14.0 – 5.0	14.0 – 9.0	9.0 – 5.0	33.0	24x27	50	RoHS CE
bg 225PAn	1		M25x1.5	9.0	20.0 – 11.0	20.0 – 16.0	16.0 – 11.0	34.0	30x34	50	RoHS CE
bg 232PAn	1		M32x1.5	11.0	25.0 – 15.0	25.0 – 20.0	20.0 – 15.0	35.0	36x41	25	RoHS CE
bg 240PAn	1		M40x1.5	12.0	32.0 – 20.0	32.0 – 26.0	26.0 – 20.0	38.0	45x49.5	10	RoHS CE
bg 250PAn	1		M50x1.5	15.0	41.0 – 31.0	41.0 – 35.0	35.0 – 31.0	47.0	57x61	5	RoHS CE
bg 263PAn	1		M63x1.5	15.0	53.0 – 41.0	53.0 – 46.0	46.0 – 41.0	49.0	70x75	5	RoHS CE