



# blueglobe – Stainless steel AISI 316Ti

Stainless steel AISI 316Ti  
Metric connection thread according to EN 60423  
With o-ring made of silicone  
Type of protection IP 68 up to 15 bar, IP 69, Type 4X  
Strain relief up to class B, EN 62444



[Request sample](#)

Material gland body	Version/colour	Material sealing insert	Colour	Temperature range (min./max.)
AISI 316Ti	Blank	TPE	Blue	-40 °C / +130 °C

Art. No.	Amount		Connection thread/length		Sealing range		Sealing range without inlet		Sealing range with inlet		Mounting height	Spanner width	SW x E	Conformity
			A	D mm	max./min. dia. mm	max./min. dia. mm	max./min. dia. mm	max./min. dia. mm						
bg 212V4A	1		M12x1.5	5.0	8.0 – 2.0	8.0 – 5.0	5.0 – 2.0	21.0	17x18.9	50	mm	CE		
bg 216V4A	1		M16x1.5	6.0	11.0 – 4.0	11.0 – 7.0	7.0 – 4.0	25.0	20x22.2	50	mm	CE		
bg 220V4A	1		M20x1.5	6.5	14.0 – 5.0	14.0 – 9.0	9.0 – 5.0	29.5	24x26.5	50	mm	CE		
bg 225V4A	1		M25x1.5	7.5	20.0 – 11.0	20.0 – 16.0	16.0 – 11.0	30.0	30x33	50	mm	CE		
bg 232V4A	1		M32x1.5	8.0	25.0 – 15.0	25.0 – 20.0	20.0 – 15.0	32.0	36x39.5	25	mm	CE		
bg 240V4A	1		M40x1.5	8.0	32.0 – 20.0	32.0 – 26.0	26.0 – 20.0	35.0	45x48	10	mm	CE		
bg 250V4A	1		M50x1.5	10.0	42.0 – 31.0	42.0 – 35.0	35.0 – 31.0	39.0	57x60	5	mm	CE		
bg 263V4A	1		M63x1.5	10.0	54.0 – 41.0	54.0 – 46.0	46.0 – 41.0	40.0	68x72	5	mm	CE		
bg 275V4A	1		M75x1.5	15.0	65.0 – 54.0	65.0 – 58.0	58.0 – 54.0	47.0	81x87	5	mm	CE		
bg 285V4A	1		M85x2.0	15.0	77.0 – 65.0	77.0 – 70.0	70.0 – 65.0	49.0	95x102	1	mm	CE		