



# blueglobe with multiple inlet – Brass

Brass, nickel-plated

Metric connection thread according to EN 60423

With o-ring made of HNBR

Type of protection IP 68 up to 15 bar, IP 69

Strain relief up to class B, EN 62444

CE RoHS

[Request sample](#)

Material gland body	Version/colour	Material sealing insert	Colour	Temperature range (min./max.)
Brass	Nickel-plated	TPE	Blue	-40 °C / +130 °C

Art. No.	Amount		Connection thread/length		Sealing range	Sealing range without inlet	Sealing range with 1 inlet	Sealing range with 2 inlets	Sealing range with 3 inlets	Spanner width
			A	D mm	max./min. dia. mm	max./min. dia. mm	max./min. dia. mm	max./min. dia. mm	max./min. dia. mm	SW x E mm
bg 225ms.3	1		M25x1.5	7.5	20.0 – 6.0	20.0 – 15.0	15.0 – 11.0	11.0 – 8.0	8.0 – 6.0	30x33
bg 225ms.3g	1		M25x1.5	7.5	20.0 – 6.0	20.0 – 15.0	15.0 – 11.0	11.0 – 8.0	8.0 – 6.0	30x33
bg 232ms.3	1		M32x1.5	8.0	25.0 – 10.0	25.0 – 19.0	19.0 – 15.0	15.0 – 12.0	12.0 – 10.0	36x39.5
bg 232ms.3g	1		M32x1.5	8.0	25.0 – 10.0	25.0 – 19.0	19.0 – 15.0	15.0 – 12.0	12.0 – 10.0	36x39.5



	Conformity

50 100%

50 100%

25 100%

25 100%