



blueglobe with multiple inlet – Stainless steel

Stainless steel AISI 303

Metric connection thread according to EN 60423

With o-ring made of silicone

Type of protection IP 68 up to 15 bar, IP 69

Strain relief up to class B, EN 62444

CE RoHS

[Request sample](#)

Material gland body	Version/colour	Material sealing insert	Colour	Temperature range (min./max.)
AISI 303	Blank	TPE	Blue	-40 °C / +130 °C

Art. No.	Amount	Connection thread/length		Sealing range	Sealing range without inlet	Sealing range with 1 inlet	Sealing range with 2 inlets	Sealing range with 3 inlets	Spanner width	•	
		A	D mm	max./min. dia. mm	max./min. dia. mm	max./min. dia. mm	max./min. dia. mm	max./min. dia. mm	SW x E mm		
bg 225VA.3	1		M25x1.5	7.5	20.0 – 6.0	20.0 – 15.0	15.0 – 11.0	11.0 – 8.0	8.0 – 6.0	30x33	5
bg 225VA.3g	1		M25x1.5	7.5	20.0 – 6.0	20.0 – 15.0	15.0 – 11.0	11.0 – 8.0	8.0 – 6.0	30x33	5
bg 232VA.3	1		M32x1.5	8.0	25.0 – 10.0	25.0 – 19.0	19.0 – 15.0	15.0 – 12.0	12.0 – 10.0	36x39.5	2
bg 232VA.3g	1		M32x1.5	8.0	25.0 – 10.0	25.0 – 19.0	19.0 – 15.0	15.0 – 12.0	12.0 – 10.0	36x39.5	2



	Conformity

0 Not CE

0 Not CE

5 Not CE

5 Not CE