



blueglobe with multiple inlet – Stainless steel AISI 316Ti

Stainless steel AISI 316Ti

Metric connection thread according to EN 60423

With o-ring made of silicone

Type of protection IP 68 up to 15 bar, IP 69

Strain relief up to class B, EN 62444

CE RoHS

[Request sample](#) 🛒

Material gland body	Version/colour	Material sealing insert	Colour	Temperature range (min./max.)
AISI 316Ti	Blank	TPE	Blue	-40 °C / +130 °C

Art. No.	Amount		Connection thread/length		Sealing range	Sealing range without inlet	Sealing range with 1 inlet	Sealing range with 2 inlets	Sealing range with 3 inlets	Spanner width	
			A	D mm	max./min. dia. mm	max./min. dia. mm	max./min. dia. mm	max./min. dia. mm	max./min. dia. mm		
bg 225V4A.3	1	🛒	M25x1.5	7.5	20.0 – 6.0	20.0 – 15.0	15.0 – 11.0	11.0 – 8.0	8.0 – 6.0	30x33	50
bg 225V4A.3g	1	🛒	M25x1.5	7.5	20.0 – 6.0	20.0 – 15.0	15.0 – 11.0	11.0 – 8.0	8.0 – 6.0	30x33	50
bg 232V4A.3	1	🛒	M32x1.5	8.0	25.0 – 10.0	25.0 – 19.0	19.0 – 15.0	15.0 – 12.0	12.0 – 10.0	36x39.5	25
bg 232V4A.3g	1	🛒	M32x1.5	8.0	25.0 – 10.0	25.0 – 19.0	19.0 – 15.0	15.0 – 12.0	12.0 – 10.0	36x39.5	25



	Conformity

0 N/A CE

0 N/A CE

5 N/A CE

5 N/A CE